

## **7.0' DSI Capacitive Touch Display**

HW Datasheet





## TFT MODULE SPECIFICATION

### **RVT70HSDNWCA0**

HB, IPS 7.0" LCD TFT display datasheet  
Rev. 1.0  
2024-12-10

---

**Riverdi Sp. z o.o.**

Nowy Swiat 36  
80-299 Gdansk, Poland  
VAT ID: PL5842767153  
Registration number (KRS): 0000923967

**+48 587 703 116**

Office hours: 9:00 to 17:30 CET (Mon-Fri)

**[contact@riverdi.com](mailto:contact@riverdi.com)**

**[riverdi.com](https://riverdi.com)**

ITEM	CONTENTS	UNIT
LCD Type	TFT/Transmissive/Normally Black/IPS	/
Size	7.0	Inch
Viewing Direction	Free	/
Outside Dimensions (W x H x D)	164.90 x 100.00 x 14.46	mm
Active Area (W x H)	154.21 x 85.92	mm
Pixel Pitch (W x H)	0.1506 x 0.1432	mm
Resolution	1024 x 600	/
Brightness	800	cd/m <sup>2</sup>
Color Depth	16.7 M	/
Pixel Arrangement	RGB Vertical Stripe	/
Driver IC of Board	SN6DSI83	/
Interface	MIPI DSI	/
EEPROM Memory Size	2-Kbit	/
Host Connector	ZIF 34 pins, 0.5mm pitch, down-side contact	/
With/Without Touch	With Projected Capacitive Touch Panel	/
CTP Driver	ILI2132A	/
Supply Voltage for Module	5.0	V
Bonding Technology	Air Bonding	/
Weight	240	g

**Note 1.** RoHS3 compliant

**Note 2.** LCM weight tolerance: ± 5%.

## 1. REVISION RECORD

REV NO.	REV DATE	CONTENTS	REMARKS
1.0	2024-12-10	Initial release	

## 2. CONTENTS

1.	REVISION RECORD .....	3
2.	CONTENTS .....	4
3.	MODULE CLASSIFICATION INFORMATION .....	5
4.	MODULE DRAWING .....	6
5.	ABSOLUTE MAXIMUM RATINGS .....	7
6.	ELECTRICAL CHARACTERISTICS .....	7
7.	BACKLIGHT ELECTRICAL CHARACTERISTICS .....	8
8.	ELECTRO-OPTICAL CHARACTERISTICS .....	9
9.	INTERFACES DESCRIPTION .....	12
9.1	TFT assignment .....	12
10.	DIAGRAM BLOCK .....	14
11.	TIMING CHARACTERISTICS .....	15
12.	CaPACITIVE TOUCH SCREEN PANEL SPECIFICATIONS .....	16
12.1	Mechanical characteristics .....	16
12.2	Electrical characteristics .....	16
13.	INSPECTION .....	17
13.1	Inspection condition .....	17
13.2	Inspection standard .....	18
14.	RELIABILITY TEST .....	20
15.	LEGAL INFORMATION .....	21
16.	CONTACT .....	22

### 3. MODULE CLASSIFICATION INFORMATION

RV	T	70	H	S	D	N	W	C	A0	V1.0A
1.	2.	3.	4.	5.	6.	7.	8.	9.	10.	11.

NO.	PARAMETER	SYMBOL
1.	BRAND	RV – Riverdi
2.	PRODUCT TYPE	T – TFT Standard
3.	DISPLAY SIZE	70 – 7.0”
4.	MODEL SERIAL NO.	H – High Brightness, IPS
5.	RESOLUTION	S – 1024 x 600 px
6.	INTERFACE	D – MIPI DSI
7.	FRAME	N – Without Mounting Metal Frame
8.	BACKLIGHT TYPE	W – LED White
9.	TOUCH PANEL	C – With Capacitive Touch Panel
10.	PCAP VERSION	A0 – aTouch, Air Bonding
11.	MODULE VERSION	V1.0A



## 5. ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Supply Voltage for Module	$V_{DD}$	0	7.4	V
Reference Voltage	$V_{REF}$	0	4.6	V
PWM Input Voltage	$V_{PWM}$	-0.3	7.4	V
Operating Temperature	$T_{OP}$	-20	70	°C
Storage Temperature	$T_{ST}$	-30	80	°C
Storage Humidity (@ 25 ± 5°C)	$H_{ST}$	10	-	% RH
Operating Ambient Humidity (@ 25 ± 5°C)	$H_{OP}$	10	-	% RH

**Note.** The above are maximum values. If exceeded, they may cause permanent damage to the unit.

## 6. ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	NOTE
Supply Voltage for Module	$V_{DD}$	-	5.0	-	V	
Reference Voltage	$V_{REF}$	0	-	3.6	V	Note 1
Current drawn from VREF	$I_{VREF}$	-	1	-	uA	$V_{REF}=1.8V$
Input High Voltage	$V_{IH}$	0.7VREF	-	-	V	
Input Low Voltage	$V_{IL}$	0	-	0.3VREF	V	
PWM Logic Input High Voltage	$V_{PWMH}$	1.2	-	VDD	V	Note 2
PWM Logic Input Low Voltage	$V_{PWML}$	0	-	0.4	V	Note 2
PWM Frequency	$F_{PWM}$	200	-	200k	Hz	Note 3

**Note 1.** TYP of reference Voltage is 1.8V or 3.3V which is dependent on the SBC.

**Note 2.** PWM input is independent of  $V_{REF}$ . Min of logic high level is 1.2V and max of logic low level is 0.4V.

**Note 3.** The backlight driver is DIO5661 and the recommended PWM frequency is 10kHz.

PARAMETER	SYMBOL	BL 0%	BL 58 %	BL 100%	UNIT	NOTE
Current drawn from $V_{DD@5.0V}$	$I_{VDD}$	194	450	737	mA	Note 3

**Note 3.**

BL 0%, current was measured with BL brightness set to 0%,  
 BL 58%, current was measured with BL brightness set to 58%,  
 BL 100%, current was measured with BL brightness set to 100%.

Test condition: ambient temperature 25°C, PCAP is in active mode. The  $I_{VDD}$  current measurement was conducted based on Dahlia Carrier board + Verdin iMX8M. Backlight levels on Verdin iMX8M can be set from 0 to 7(8 levels).

BACKLIGHT LEVEL	0%	14.5%	29%	43.5%	58%	72.5%	85.5%	100%
SOM BL SET	0	1	2	3	4	5	6	7

## 7. BACKLIGHT ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	NOTE
Lifetime	-	-	50,000	-	hours	Note 1

**Note 1.** Unless specified, the ambient temperature  $T_a = 25^\circ\text{C}$

**Note 2.** The recommended operating conditions refer to a range in which operation of this product is guaranteed. The operation cannot be guaranteed if the absolute maximum values exceed.

**Note 3.** If LED is driven by high current, high ambient temperature and humidity condition, the lifetime of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating lifetime is estimated data.

## 8. ELECTRO-OPTICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN	TYP	MAX	UNIT	RMK	NOTE
Response Time	Tr+Tf	$\theta=0^\circ$ $\phi=0^\circ$ Ta=25 °C	-	25	35	ms	FIG 1.	4, 7
Contrast Ratio	Cr		800	1000	-	---	FIG 2.	1, 7
Surface Luminance	Lv		-	800	-	cd/m <sup>2</sup>		2, 7
Viewing Angle Range	$\theta$	$\phi = 90^\circ$	75	85	-	deg	FIG 3.	6
		$\phi = 270^\circ$	75	85	-	deg		
		$\phi = 0^\circ$	75	85	-	deg		
		$\phi = 180^\circ$	75	85	-	deg		
CIE (x, y) Chromaticity	Rx	$\theta=0^\circ$ $\phi=0^\circ$ Ta=25 °C	0.578	0.618	0.658	-	FIG 2.	5,7
	Ry		0.489	0.329	0.369	-		
	Gx		0.376	0.416	0.456	-		
	Gy		0.493	0.533	0.573	-		
	Bx		0.071	0.111	0.151	-		
	By		0.108	0.148	0.188	-		
	Wx		0.270	0.310	0.350	-		
	Wy		0.290	0.330	0.370	-		

**Note 1.** Contrast Ratio (CR) is defined mathematically as below, for more information see Figure 2.

$$\text{Contrast Ratio} = \frac{\text{Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}{\text{Average Surface Luminance with all black pixels (P1, P2, P3, P4, P5)}}$$

**Note 2.** Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information see Figure 2.

$$Lv = \text{Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}$$

**Note 3.** The uniformity in surface luminance  $\delta$  WHITE is determined by measuring luminance at each test position 1 through 5, and then dividing the minimum luminance of 5 points luminance by maximum luminance of 5 points luminance. For more information see Figure 2.


$$\delta \text{ WHITE} = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}$$

**Note 4.** Response time is the time required for the display to transition from white to black (Rise Time,  $T_r$ ) and from black to white (Decay Time,  $T_f$ ). For additional information see Figure 1. The test equipment is BM-7A.


**Note 5.** CIE (x, y) chromaticity, the x, y value is determined by measuring luminance at each test position 1 through 5, and then make average value.

**Note 6.** For TFT module, viewing angle is the angle at which the contrast ratio is greater 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to LCD surface. For more information see Figure 3.


**Note 7.** Viewing angle is measured at the center point of the LCD by CONOSCOPE (ergo-80). For response time testing, the testing data is based on BM-7A. Instruments for Contrast Ratio, Surface Luminance, Luminance Uniformity, Chromaticity the test data is based on SR-3A.



*Figure 1. The definition of response time*



*Figure 2. Measuring method for Contrast ratio, surface luminance, Luminance uniformity, CIE (x, y) chromaticity*



*Figure 3. The definition of viewing angle*

## 9. INTERFACES DESCRIPTION

### 9.1 TFT assignment

PIN	SYMBOL	I/O	DESCRIPTION	NOTE
<b>1</b>	GND	P	Ground	
<b>2</b>	DSI_D0P	I/O	MIPI DSI differential data pair. (Data lane 0)	
<b>3</b>	DSI_D0N	I/O		
<b>4</b>	GND	P	Ground	
<b>5</b>	DSI_D1P	I	MIPI DSI differential data pair. (Data lane 1)	
<b>6</b>	DSI_D1N	I		
<b>7</b>	GND	P	Ground	
<b>8</b>	DSI_CLKP	I	MIPI DSI differential clock pair	
<b>9</b>	DSI_CLKN	I		
<b>10</b>	GND	P	Ground	
<b>11</b>	DSI_D2P	I	MIPI DSI differential data pair. (Data lane 2)	
<b>12</b>	DSI_D2N	I		
<b>13</b>	GND	P	Ground	
<b>14</b>	DSI_D3P	I	MIPI DSI differential data pair. (Data lane 3)	
<b>15</b>	DSI_D3N	I		
<b>16</b>	GND	P	Ground	
<b>17</b>	PWR_DN	I	Power down (With locally generated reset after releasing power-down) Active Low, display is off when signal is low;	Note 2
<b>18</b>	PWM	I	Backlight brightness control	Note 3
<b>19</b>	INT	O	Touch panel Interrupt signal; Open-drain output, active low	Note 2

20	I2C_SCL	I	I2C clock signal	Note 2
21	I2C_SDA	I/O	I2C data signal	
22	RESET	I	Touch panel reset	
23	NC	/	No connection	
24	V <sub>REF</sub>	P	Reference voltage	
25	NC	/	No connection	
26	5.0V	P	Power supply V <sub>DD</sub>	
27				
28				
29				
30	GND	P	Ground	
31	NC	/	No connection	
32				
33				
34				

**Note 1.** Matched 34 pins, 0.5 mm pitch, 150 mm long FFC accessory: FFC0534150


**Note 2.** Internally pull-up with 15K resistors to V<sub>REF</sub> for pins 17, 19  
Internally pull-up with 10K resistors to V<sub>REF</sub> for pins 20, 21

**Note 3.** The backlight driver is DIO5661. PWM frequency range: 200Hz – 200KHz and the recommended PWM frequency is 10kHz.

0% PWM duty cycle corresponds to minimum brightness.

100 PWM duty cycle corresponds to maximum brightness.

## 10. DIAGRAM BLOCK



## 11. TIMING CHARACTERISTICS

The TFT of the module applies Riverdi high brightness, IPS, 7.0" TFT: RVT70HSLNWCA0

For detailed information of the display, please refer to the datasheet of display.

PARAMETER	SYMBOL	VALUE			UNIT
		MIN.	TYP.	MAX.	
DCLK frequency (Frame rate 60Hz)	Fclk	40.8	51.2	67.2	MHz
Horizontal display area	Thd	1024			DCLK
HSYNC period time	Th	1114	1344	1400	
HSYNC blanking	Thb+Thfp	90	320	376	
Vertical display area	Tvd	600			H
VSYNC period time	Tv	610	635	800	
VSYNC blanking	Tvb+Tvfp	10	85	200	

## 12. CAPACITIVE TOUCH SCREEN PANEL SPECIFICATIONS

### 12.1 Mechanical characteristics

DESCRIPTION	SPECIFICATION	REMARK
<b>Touch Panel Size</b>	7.0 inch	αTouch
<b>Outline Dimension of CTP</b>	164.70 mm x 99.80 mm	
<b>Product Thickness</b>	2.45 mm	
<b>Glass Thickness</b>	1.1 mm	
<b>CTP View Area</b>	155.01 mm x 86.72 mm	
<b>Sensor Active Area</b>	156.08 mm x 88.42 mm	
<b>Surface Hardness</b>	7H	

### 12.2 Electrical characteristics

DESCRIPTION	SPECIFICATION	REMARK
<b>Linearity</b>	+/-1.5mm	
<b>Controller</b>	ILI2132A	
<b>Resolution</b>	1024 x 600	

## 13. INSPECTION

Standard acceptance/rejection criteria for TFT module


### 13.1 Inspection condition

Ambient conditions:



- Temperature:  $25 \pm 2^{\circ}\text{C}$
- Humidity:  $(60 \pm 10) \% \text{RH}$
- Illumination: Single fluorescent lamp non-directive (300 to 700 lux)

Viewing distance:  $35 \pm 5\text{cm}$  between inspector bare eye and LCD.

Viewing Angle: U/D:  $45^{\circ}/45^{\circ}$ , L/R:  $45^{\circ}/45^{\circ}$



## 13.2 Inspection standard

ITEM	CRITERION		
Black spots, white spots, light leakage, Foreign Particle (round Type)	 $D=(x+y)/2$ Spots density: 10 mm	Size = 7.0"	
		Average Diameter	Qualified Qty
		$D \leq 0.2 \text{ mm}$	Ignored
		$0.2 \text{ mm} < D \leq 0.3 \text{ mm}$	$N \leq 3$
		$0.5 \text{ mm} < D$	Not allowed
LCD black spots, white spots, light leakage (line Type)	 Spots density: 10 mm	Size = 7.0"	
		Length	Width Qualified Qty
		-	$W \leq 0.05$ Ignored
		$L \leq 5.0$	$0.05 < W \leq 0.1$ 3
		$5.0 < L$	$0.1 < W$ Not allowed
Bright/Dark Dots	Size = 7.0"		
	Item		Qualified Qty
	Bright dots		$N \leq 2$
	Dark dots		$N \leq 3$
	Total Bright and Dark Dots		$N \leq 4$
Clear spots	Size $\geq 5.0$ "		

	Average Diameter		Qualified Qty
	$D < 0.2 \text{ mm}$		Ignored
	$0.2 \text{ mm} < D < 0.3 \text{ mm}$		4
	$0.3 \text{ mm} < D < 0.5 \text{ mm}$		2
	$0.5 \text{ mm} < D$		0
	Spots density: 10 mm		
Touch panel spots	Size $\geq 5.0''$		
	Average Diameter		Qualified Qty
	$D < 0.25 \text{ mm}$		Ignored
	$0.25 \text{ mm} < D < 0.5 \text{ mm}$		4
	$0.5 \text{ mm} < D$		0
Touch panel white line scratch	Size $\geq 5.0''$		
	Length	Width	Qualified Qty
	-	$W \leq 0.03$	Ignored
	$L \leq 5.0$	$0.03 < W < 0.05$	2
	-	$0.05 < W$	0

## 14. RELIABILITY TEST

NO.	TEST ITEM	TEST CONDITION	NOTE
1	High Temperature Storage	80°C/120 hours	Note 1
2	Low Temperature Storage	-30°C/120 hours	
3	High Temperature Operating	70°C/120 hours	
4	Low Temperature Operating	-20°C/120 hours	
5	High Temperature and High Humidity	40°C, 90%RH, 120Hrs	
7	Thermal Cycling Test (No operation)	-20°C for 30min, 70°C for 30 min. 100 cycles. Then test at room temperature after 1 hour	Note 2
8	Vibration Test	Frequency: 10 ÷ 55 Hz. Stroke: 1.5 mm. Sweep: 10Hz ÷ 55Hz ÷ 10 Hz. 2 hours for each direction of X, Y, Z (Total 6 hours)	
9	Package Drop Test	Height: 60 cm 1 corner, 3 edges, 6 surfaces	

**Note 1.** Sample quantity for each test item is 5 ÷ 10 pcs.

**Note 2.** The device is kept at room temperature for 2 hours prior to starting the test

## 15. LEGAL INFORMATION

CE marking is usually obligatory only for a complete end product. Riverdi display modules are semi-finished goods which are used as inputs to become part of the finished products.

Therefore, Riverdi display modules are not CE marked.

This is not a standalone product. It was designed as an electronic component. It needs integration with a whole system to be fully functional.

Riverdi grants the guarantee for the proper operation of the goods for a period of 12 months from the date of possession of the goods. If in a consequence of this guaranteed execution the customer has received the defects-free item as replacement for the defective item, the effectiveness period of this guarantee shall start anew from the moment the customer receives the defects-free item.

Information about device is the property of Riverdi and may be the subject of patents pending or granted. It is not allowed to copy or disclosed this document without prior written permission.

Riverdi endeavors to ensure that all contained information in this document is correct but does not accept liability for any error or omission. Riverdi products are in developing process and published information may be not up to date. Riverdi reserves the right to update and makes changes to Specifications or written material without prior notice at any time. It is important to check the current position with Riverdi.

Images and graphics used in this document are only for illustrative the purpose. All images and graphics are possible to be displayed on the range products of Riverdi, however the quality may vary. Riverdi is no liable to the buyer or to any third party for any indirect, incidental, special, consequential, punitive, or exemplary damages (including without limitation lost profits, lost savings, or loss of business opportunity) relating to any product, service provided or to be provided by Riverdi, or the use or inability to use the same, even if Riverdi has been advised of the possibility of such damages.

Riverdi products are not fault tolerant nor designed, manufactured or intended for use or resale as on line control equipment in hazardous environments requiring fail-safe performance, such as in the operation of nuclear facilities, aircraft navigation or communication systems, air traffic control, direct life support machines or weapons systems in which the failure of the product could lead directly to death, personal injury or severe physical or environmental damage ('High-Risk Activities'). Riverdi and its suppliers specifically disclaim any expressed or implied warranty of fitness for High-Risk Activities. Using Riverdi products and devices in 'High-Risk Activities' and in any other application is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Riverdi from all damages, claims or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Riverdi intellectual property rights.

## 16. CONTACT

### Your Success is Our Priority

Stuck on a technical challenge? Need expert guidance?  
Our dedicated support team is just a message away.

Contact us at  
[contact@riverdi.com](mailto:contact@riverdi.com)

We're here to ensure your project's success, every step of the way!